



## SPECIFICATION SHEET

### COMMERCIAL RUBBER

A general purpose, relatively cheap rubber material that is suitable for low/medium duty applications. Available in a vast hardness range and displaying excellent physical properties including abrasion resistance, good tensile strength and low compression set. Excellent low temperature properties. Unsuitable for use with solvents including aliphatic and aromatic hydrocarbons, including lubricating oil and petrol.

<b>ELASTOMER</b>	-	<b>NATURAL</b>
<b>COLOUR</b>	-	<b>BLACK</b>
<b>QUALITY</b>	-	<b>COMMERCIAL</b>
<b>GRADE</b>	-	<b>N02</b>
<b>HARDNESS</b>	-	<b>70° SHORE A</b>
<b>S.G.</b>	-	<b>1.55G/CM<sup>3</sup></b>
<b>TENSILE MPA</b>	-	<b>4</b>
<b>ELONGATION</b>	-	<b>300%</b>
<b>TEAR STRENGTH</b>	-	<b>12 KG/CM</b>
<b>COMPRESSION SET</b>	-	<b>43%</b>
<b>ABRASION RESISTANCE</b>	-	<b>48/0 MM<sup>3</sup></b>
<b>OPERATING TEMPERATURE</b>	-	<b>-20° / +70° C</b>

\*\*The information given above is based upon average values and is no way intended as a warranty. The purchaser is deemed responsible for determining the suitability of the product for any particular application. All data relating to suitable uses and description information concerning our products are compiled from research and are believed to be reliable, but are provided for guidance purposes only. The Company holds no legal or contractual responsibility for information supplied\*\*.