

RH Nuttall Limited

Great Brook Street
Nechells Green
Birmingham B7 4EN

e: sales@rhnutall.co.uk
t: 0121 359 2484
f: 0121 359 4439

Material Specification Sheet

RHN 46H



www.rhnutall.co.uk

DOUBLE SIDED TAPE 4610

Product description:

A solvent - free modified acrylic adhesive, NH adhesive has excellent direct tack, and continuous adhesion on both closed and open cell foam – type surfaces. For example, Polyethylene (PE), Polyurethane (PUR), and Polyether and Polyester (PET) based foams. The adhesive has good resistance to temperature, UV and ageing.

PRODUCT CODE REFERENCE	RHN 46H
CARRIER	SCRIM PES/PVA
BACKING PAPER	HONEY/LIGHT BROWN, RELEASE COATED, 90 GRAMMES PER SQ. METRE
TOTAL THICKNESS WITHOUT BACKING	100 MICRONS
ADHESION TO STEEL (AFERA 4001)	16 N/25 MM
DYNAMIC SHEAR	0.16 N/SQ. MM
ADHESIVE COAT WEIGHT	90 GRAMMES PER SQ. METRE
TEMPERATURE RESISTANCE	-40 C TO +100 C

****The information given above is based upon average values and is no way intended as a warranty. The purchaser is deemed responsible for determining the suitability of the product for any application. All data relating to suitable uses and description information concerning our products are compiled from research and are believed to be reliable but are provided for guidance purposes only. The Company holds no legal or contractual responsibility for information supplied****

