

RH Nuttall Limited

Great Brook Street
Nechells Green
Birmingham B7 4EN

Material Specification Sheet

e: sales@rhnutall.co.uk
t: 0121 359 2484
f: 0121 359 4439

RHN 19A



www.rhnutall.co.uk

White Wool Felt – 25 Density

General Information & Applications

Felt products are used in a variety of applications ranging from the automotive industry, to musical instruments. It is also used throughout the construction industry. Felt is also often used as a damper in the automotive industry where it deadens the rattle between certain components. Furthermore, it also stops dirt entering certain types of ball joints. Adhesive backing can be applied to any felt product.

Property	Result
Density	0.25gm/CC
Tolerance 3mm and below	+/- 20%
3.1 to 10.0mm	+/- 15%
above 10.0mm	+/- 10%
Colour	Natural White
Composition	Wool 50% (nominal)
	Viscose 50%
Thickness	1.0 to 25.0 (1/16" to 1")
Tolerance 3mm and below	+/- 20%
3.1 to 10.0mm	+/- 15%
above 10.0mm	+/- 10%
Width	1800mm
BS Specification	Tolerances to BS.4060

The information given above is based upon average values and is no way intended as a warranty. The purchaser is deemed responsible for determining the suitability of the product for any application. All data relating to suitable uses and description information concerning our products are compiled from research and are believed to be reliable but are provided for guidance purposes only. The Company holds no legal or contractual responsibility for information supplied

