

RH Nuttall Limited

Great Brook Street
Nechells Green
Birmingham B7 4EN

Material Specification Sheet

e: sales@rhnutall.co.uk
t: 0121 359 2484
f: 0121 359 4439

RHN 19E



www.rhnutall.co.uk

Black Admiral Felt

General Information

Lower cost than wool felt.
Bonds to adhesive very well.
Stable at ambient temperatures up to 150°C
Will pass Automotive Flame Standard FMVSS302
Tighter tolerances than pressed felt
Non-stretch & UV stable.

Thicknesses

1mm; 1.5mm; 2mm; 3mm

Property	Result
Density	180gm/sqm
Tolerances	Weight/Thickness $\pm 20\%$
Colour	Black
Composition	100% Polyester
Type (felt)	Unsupported needle loom
Reaction to Flame	Passes FMVSS302
Width	920mm
Chemical Resistance (acids/alkalis)	Poor
Ozone Resistance	Good
Specifications	Unclassified

The information given above is based upon average values and is no way intended as a warranty. The purchaser is deemed responsible for determining the suitability of the product for any application. All data relating to suitable uses and description information concerning our products are compiled from research and are believed to be reliable but are provided for guidance purposes only. The Company holds no legal or contractual responsibility for information supplied

