

RH Nuttall Limited

Great Brook Street
Nechells Green
Birmingham B7 4EN

Material Specification Sheet

e: sales@rhnutall.co.uk
t: 0121 359 2484
f: 0121 359 4439

RHN 1007



www.rhnutall.co.uk

Pre-Compressed Expanding Foam Tape

Property	Result
Density	Approx. 120g/m ³ (+10%)
Colour	Black
Compression resistance	Approx. 5.0 kPa
Tensile strength	Approx. 170 Pa
Elongation	Approx. 170%
Temperature range	-40/100°C shortly to +130°C DIN 1748-2
Acceptance to other building materials	Extremely good - DIN 52452
Fire resistance	PASS B1 DIN 4102
Water penetration (600 Pascal's)	PASS EN 86
Water vapour resistance	< 100μ DIN 52452
Thermal Conductivity	PASS B1 DIN 4102
Air Penetration	PASS EN 86
Resistance to ageing	PASS DIN 53387
Storage time	1 year (in ambient temperature)
Mounting temperature	+5 to 30°C
Storage temperature	+10 to +20°C
Life expectancy	25 years

****The information given above is based upon average values and is no way intended as a warranty. The purchaser is deemed responsible for determining the suitability of the product for any application. All data relating to suitable uses and description information concerning our products are compiled from research and are believed to be reliable but are provided for guidance purposes only. The Company holds no legal or contractual responsibility for information supplied****

