

RH Nuttall Limited

Great Brook Street
Nechells Green
Birmingham B7 4EN

Material Specification Sheet

e: sales@rhnutall.co.uk
t: 0121 359 2484
f: 0121 359 4439

RHN 11G



www.rhnutall.co.uk

Soft Grade Expanded Closed Cell EPDM Sponge

Description	Standard	Value	Unit
ASTM D1056-14 Classification	2A1 B3		
Density	ASTM D3575	70-100	Kg/m ³
Compression Deflection (25%)	ASTM D1056	20-40	kPa
Compression Deflection (50%)	ASTM D1056	50-70	kPa
Compression Set (25%/22h/23°C) After 24h	ASTM D1056	13-18	%
Compression Set (50%/22h/23°C) After 24h	ASTM D1056	30-45	%
Shrinkage (22h/70C)	ASTM D573	12-17	%
Shore Hardness		35-45	OO
Elongation	ASTM D412	150-180	%
Temperature Range (Constant)		-20/+70	°C
Temperature Range (Intermittent)		+90	°C
Water Absorption (Max Weight Change)	ASTM D1056	1-3	%
Tensile Strength	ASTM D412	300-350	kPa
Environmental Protection		CFC, Halogen & HCFC Free	

The information given above is based upon average values and is no way intended as a warranty. The purchaser is deemed responsible for determining the suitability of the product for any application. All data relating to suitable uses and description information concerning our products are compiled from research and are believed to be reliable but are provided for guidance purposes only. The Company holds no legal or contractual responsibility for information supplied

