

RH Nuttall Limited

Great Brook Street
Nechells Green
Birmingham B7 4EN

e: sales@rhnutall.co.uk
t: 0121 359 2484
f: 0121 359 4439

Material Specification Sheet

RHN 19H



www.rhnutall.co.uk

40W Pressed Woollen Felt

An off white woollen felt, containing minimum 90% wool content.

Designation BS4060 2006 A97/3W ABA3.

Colour	Off White
Weight	400gmm/Square Meter/1mm Thick
Density, Din 61200	0.40g/Cm3
Width ISO 3932	153cm-160cm
Thickness Din 61206	2mm,3mm,6mm,10mm,12mm,16mm
Tensile Strength	Min 1000 Kn/M2
Ph	Neutral 5 To 8
Max Shrinkage In Water	10%
Max Swelling In Water	20%
Min Oil Retention	150%
Tolerances	As BS4060 1989 Table 2
Reaction To Fire	Not Readily Combustible-Upper Limited 140°C

Stored in clean dry conditions, preferably off floor level in seal bags.

Please note, mildew can occur if felts become damp and unproofed.

****The information given above is based upon average values and is no way intended as a warranty. The purchaser is deemed responsible for determining the suitability of the product for any application. All data relating to suitable uses and description information concerning our products are compiled from research and are believed to be reliable but are provided for guidance purposes only. The Company holds no legal or contractual responsibility for information supplied****

