

RH Nuttall Limited

Great Brook Street
Nechells Green
Birmingham B7 4EN

e: sales@rhnutall.co.uk
t: 0121 359 2484
f: 0121 359 4439

Material Specification Sheet

RHN 46X



www.rhnutall.co.uk

DOUBLE SIDED TISSUE TAPE

High temperature acrylic tissue tape on a yellow release liner, typically used for splicing and foam laminating applications.

Based on supplier information the components of the adhesive conform to the compositional requirements of F&DA 175.105 for indirect food contact. Additional to this compliance there should also be a functional barrier between adhesive and the food. Such functional barrier and determination of suitability are the responsibility of the customer.

Recommended application temperature: 5°C (41°F) to 60°C (140°F)

Liner Type

Yellow glassine

Mechanical Properties

Liner	80g yellow siliconised release paper
Carrier	13g tissue
Adhesive	Acrylic based with 45gsm on both open and closed sides
Total Thickness	115 micron

General Characteristics

Peel Adhesion to Steel (24hrs dwell)	Protected 650 N/M	Open 650 N/M
Shear Adhesion to Steel	Protected 50 hrs	Open 50 hrs
Shelf Life	Recommended 12 months from supply	

This adhesive backing is generally described as a fixing aid rather than a permanent fixing. However, customers are advised to test suitability for their specific applications.

The information given above is based upon average values and is no way intended as a warranty. The purchaser is deemed responsible for determining the suitability of the product for any application. All data relating to suitable uses and description information concerning our products are compiled from research and are believed to be reliable but are provided for guidance purposes only. The Company holds no legal or contractual responsibility for information supplied

